


ASSEMBLY PART NUMBER	(A)	(ØB)	(ØC)	(ØD)	E ±.050	F	G ±1°	L1 ±.060	L2 ±.060	L3 ±.060	(L4)
PLK1650D1616	10.000	2.000	2.000	3.000	3.500	3.000	30°	.781	--	.291	8.750
PLK1650D1624	10.000	2.000	2.500	3.750	3.250	3.500	30°	.938	--	.787	8.750
PLK1650D2424	10.000	2.500	2.500	3.750	3.250	3.500	30°	.788	--	.742	9.750
PLK1650D2432	10.000	2.500	3.000	4.375	3.000	4.000	30°	1.062	--	.694	9.750
PLK16502432E20	10.000	2.500	3.000	4.375	3.000	4.000	20°	.793	--	.596	9.750
PLK1650D3232	10.000	3.000	3.000	4.375	3.000	4.000	30°	.772	--	.041	9.750
PLK1650D3232E20	10.000	3.000	3.000	4.375	3.000	4.000	20°	.793	1.283	--	11.000
PLK1650D3240	10.000	3.000	3.750	5.000	2.625	4.750	30°	.867	--	.390	9.750
PLK1650D3248	11.750	3.000	4.375	5.500	3.188	5.375	30°	1.492	--	1.390	9.750
PLK1650D4040	10.000	3.750	3.750	5.000	2.625	4.750	30°	1.076	1.180	--	11.000
PLK1650D4048	11.750	3.750	4.375	5.500	3.188	5.375	30°	1.188	--	.563	11.000
PLK1650D4064	11.750	3.750	5.500	7.500	2.875	6.000	30°	2.414	--	2.803	11.250
PLK1650D4848	11.750	4.375	4.375	5.500	3.188	5.375	30°	.750	3.403	--	11.250
PLK1650D4880	17.000	4.375	6.500	8.000	5.250	6.500	30°	2.071	--	1.706	9.750
PLK1650D5656	11.750	5.000	5.000	7.000	2.875	6.000	30°	1.393	.960	--	11.250
PLK1650D6480	17.000	5.500	6.500	8.000	5.250	6.500	30°	1.600	--	.654	11.250
PLK1650D8096	26.500	6.500	8.000	10.000	8.750	9.000	30°	2.153	--	.422	13.500
PLK1650D9696	26.500	8.000	8.000	10.000	8.750	9.000	30°	1.635	4.352	--	24.000

THIS DRAWING AND THE INFORMATION CONTAINED HEREIN ARE THE PROPERTY OF DMC POWER AND SHALL NOT BE COPIED, REPRODUCED OR DISCLOSED WITHOUT EXPRESS AUTHORIZATION BY DMC POWER.



LEGEND

PLK1650	D	XX	YY	
└──	└──	└──	└──	MAIN RUN BUS SIZE IDENTIFIER
	└──	└──	└──	TAB BUS SIZE IDENTIFIER
	└──	└──	└──	MATERIAL CODE: D = ALUMINUM
└──				BASIC P/N

THIS DRAWING AND THE INFORMATION CONTAINED HEREIN ARE THE PROPERTY OF DMC POWER AND SHALL NOT BE COPIED, REPRODUCED OR DISCLOSED WITHOUT EXPRESS AUTHORIZATION BY DMC POWER.